




Technology as a passion.

# Transcar RS-SN

25 - 28 - 33 - 40 

60 SL  - 70 SL 



## technical table



GOLDONI S.p.A.



# Transcar RS-SN

25 - 28 - 33 - 40

60 SL - 70 SL

		Transcar 25 (SN & RS)	Transcar 28 (SN & RS)	Transcar 33 (SN & RS)	Transcar 40Q (SN & RS)	Transcar 60 SL Q (SN & RS)	Transcar 70 SL Q (SN & RS)		
Engine	Type	Diesel		Diesel		Diesel direct injection			
	Power rating / nominal rate	kW(hp) rpm	16 (22) - 3000	18 (25) - 2800	25 (34) - 2800	27 (37) - 2800	35 (48) - 2600	49 (67) - 2600	
	N° cylinders	n°	2		3		3 turbo		
	Cooling		Air		Water				
	Swept volume	cc	954	1248	1551	1649	2082	2082	
	Torque reserve		15%	12%	14%	14%	13%	25%	
	Tank capacity	lt	38	38	38	38	38	38	
Transmission	Type	Smooth mesh with easy shift	Synchronized, constant mesh gears						
	N° speeds		6+3	8+4		8+8			
	Main clutch		Single disc dry clutch with torsional damper						
	Reverse shuttle		/	/	/	Yes	Yes	Yes	
	Rear differential lock		Mechanical rear lock	Hydraulic rear lock		Hydraulic lock on both axles			
	Speed	Kph	30			40			
Drive		4 WD with possibility to mechanically disconnect the rear drive							
Brakes and Steering	Service brake	Hydraulic brake, acting on 4 wheels with double separate circuit. Brake drums							
	Parking and emergency brake	Acting on rear wheels. Mechanic control, fully independent from service brake							
	Type of steering	Hydrostatic							
	Steering angle	m	SN: 4 - RS: 5,25			SN: 4,25 - RS: 5,50			
Rear PTO	Type	540 rpm, anticlockwise rotation. Profile 26 UNI 220			540 rpm, clockwise rotation. Profile 1" 3/8				
	Clutch	7,5"			8,5"		11"		
	Control	Mechanical							
Electric system	Voltage	Volts	12						
	Battery	A/h	80						
Towing	Rear tow hook	Class B							
	Max towing weight allowed	Kg	3800	3800	3800	4800	5010	5010	

		Transcar 25		Transcar 28		Transcar 33		Transcar 40 Quadrifoglio		Transcar 60 SL Quadrifoglio		Transcar 70 SL Quadrifoglio		
		SN	RS	SN	RS	SN	RS	SN	RS	SN	RS	SN	RS	
Dimensions	A	mm	4110	4110	4110	4110	4210	4210	4490	4790	4600	4900	4600	4900
	C	mm	2050	2050	2050	2050	2050	2050	2280	2580	2280	2580	2280	2580
	F	mm	1270-1500	1390-1500	1270-1500	1390-1500	1270-1500	1390-1500	1440-1560	1490-1550	1440-1560	1490-1550	1440-1560	1490-1550
	G	mm	2025	2025	2025	2025	2025	2025	2160	2160	2160	2160	2160	2160
	N	mm	265	265	265	265	265	265	265	265	265	265	265	265
	P	mm	/	1975	/	1975	/	1975	/	2020	/	2020	2020	2020
Weight*	●	Kg	3500		3500		3500		3500		4500		4500	
	●	Kg	1520	1550	1520	1550	1610	1630	1670	1880	1770	1940	1770	1940
	●	Kg	/	/	/	/	/	1860	/	1970	/	2065	/	2065

\*Weights are with bed

■ Full load weight  
■ Net weight

● Approved for road circulation  
● Weight with safety frame  
● Weight with cab

A - Length  
C - Wheelbase  
F - Width min. and max.  
G - Height to safety frame  
N - Ground clearance  
P - Height to cab



Goldoni S.p.A.

Via Canale, 3 - 41012 Migliarina di Carpi - Modena, Italy  
tel. +39 0522 640 111 - fax +39 0522 699 002 - www.goldoni.com

Authorized dealer

0640 - 06430706

Goldoni S.p.A. reserves the right to change specification, design and price of products described in this literature without notice.